

FIRST BOAT NAHE WATER WINS.

SUNSTREAM HELPS YOU ENJOY YOUR BOAT MORE.

Boating is our passion and, like you, we envisioned a future that minimized the hassles and frustrations of getting your boat in and out of water, accessing the hull and covering the boat. For over 25 years, we've been leading the industry by elevating boating experiences all over the globe. Our award winning engineering and design continue to push the boundaries of what's possible by producing many of the world's first freestanding hydraulic boat lifts and automatic cover systems. You're invited to the future of boating.

 free-standing Hydraulic lift
free-floating Hydraulic lift

Boat more, boat easier, boat better.



SUNLIFT X The Best Just Got Better.

The Sunlift X is the new standard in free-standing hydraulic boat lifts. Sunstream has a rich heritage of innovation and it continues to drive us today more than ever. We're boaters too and we believed boating could be more fun and less hassle. The Sunlift X is the culmination of meticulous engineering, unparalleled manufacturing and technological advancement.

Well designed to lift boats and drop jaws.





- 1 Adjustable Width Bunks
- 2 Adjustable Range Option
- 3 Side Shift
- 4 Stainless Steel Cylinders & Hoses

- 5 Hydraulic Boot & Scrubber
- 6 Cylinders Aligned with Frame
- 7 Soft Stop
- 8 Bronze Bushings

- 9 Stylish Domed Head Pins
- 10 Set Bolt in Leg Sleeves
- 11 Oval Cast Feet
- 12 SuperBunks[™]

- 13 3.25in Wide Beams
- 14 Thick Wall Aluminum Construction
- 15 Bronze Nuts
- 16 GravityLock[™]

FLAWLESS HULL FIT

The SunLift X is the only hydraulic lift that has adjustable width bunks to achieve an ideal boat fit. Additionally, the boat height over water can be set with an adjustable lifting range up to 6.5 feet. The frame can also shift laterally to minimize the distance of the boat to dock to allow safe boarding every time. Sunstream SuperBunks[™] softly cradle the hull and will last for years without wear. The Superbunks[™] act as spring beams, which spread the load over the entire bunk, creating a comfortable resting spot for your boat without pressure points.

PREMIUM HYDRAULICS

The hydraulic system is the heart of a hydraulic lift and is key for reliability and performance. The SunLift X does not compromise with superior durability with all stainless steel cylinders with SoftStop[™], a patented shaft boot, double braid stainless hoses, and stainless fittings. The SunLift X has the best performance with the premium pressure balance pump (versus a basic fixed gear pump) that has up to 20% greater efficiency, higher speed, quieter sound, and does not lose lifting capacity over time. The American built blue anodized power unit has premium German valves and a unique pressure relief at the bottom prevents hydraulic lock. The system uses a non-oil, water soluble SunFluid, which is far more durable against water intrusion versus oil.

MODERN FRAME

The SunLift X modern frame has a beauty that is worthy of displaying your boat. The frame has superior stiffness with the cylinders aligned with frame, fewer bolts, and a set bolt to remove movement in the leg socket. The SunLift X boasts the best range of specifications on the market, with the highest lifting range, shallowest water depth, fastest speed, and capacities to 30,000lbs. Optional Leg Jacks can give an additional 3ft of range to lakes with seasonal fluctuation. The over-center GravityLock[™] gives you maximum peace of mind.





Optional bow stop shown

BLUETOOTH & APP

Sunstream's optional Bluetooth transmitter and smartphone app give you the power to lift your boat with your phone! It also gives important lift diagnostics to prevent a problem from becoming a problem. Bluetooth technology has more consistent range, and is more responsive. Built-in security features protect your boat, and 'depressurize' is ideal for seasonal users.



SWIFTSHIELD

Sunstream's SwiftShield automatic boat cover system helps you to use your boat more and protects your investment. Say farewell to the frustration that comes with traditional boat covers and hello to boating anytime you want. Be on the water in just 30 seconds with the push of a remote.

SPECIAL CONFIGURATIONS





Shallow Water SW

Pontoon/Tritoon Lifting with Toons PON





Pontoon/Tritoon Underdeck Lifting UDK **3' Range** B3

Patents: US5908264A, US11932364B2, US20210354794A1, CA3179256A1, APP 18/597736, WO2021236694A1, 29/821,521, 29/821,417, 29/821,372, 29/821,357, 29/821,375, 29/821,355, US6976442B2, US7246970B2, US8683912B2, CA2750606C, US10011326B2, US8911174B2, US8911174B2

	MEDIUM Family B			LARGE Family B			X-LARGE Family C				
	SLX5010B4	SLX6512B4	SLX8012B4	SLX9012B5	SLX10014B5	SLX12016B5	SLX16018C5	SLX20020C5	SLX24022C5	SLX30022C5	
Capacity at	5,000lb	6500lb	8000lb	9000lb	10000lb	12000lb	16000lb	20000lb	24000lb	30000lb	
Standard Range	2268kg	2948kg	3629kg	4082kg	4536kg	5443kg	7257kg	9072kg	10886kg	13608kg	
Standard Range	4ft	4ft	4ft	5ft	5ft	5ft	5ft	5ft	5ft	5ft	
	1.2m	1.2m	1.2Mm	1.52m	1.52m	1.52m	1.52m	1.52m	1.52m	1.52m	
Bunk Length	10ft	12ft	12ft	12ft	14ft	16ft	18ft	20ft	22ft	22ft	
	Зm	3.7m	3.7m	3.7m	4.2m	4.9m	5.5m	6m	6.7m	6.7m	
Frame Width*	102.5in	102.5in	132.5in	132.5in	132.5in	132.5in	152.5in	152.5in	152.5in	152.5in	
	260.3cm	260.3cm	336.5cm	336.5cm	336.5cm	336.5cm	387.3cm	387.3cm	387.3cm	387.3cm	
Frame Length**	120.5in	144.4in	144.8in	145.9in	169.4in	193.4in	173.6in	197.6in	221.6in	221.6in	
	306cm	366.7cm	367.7cm	370.5cm	430.2cm	491.2cm	440.9cm	501.9cm	562.8cm	562.8cm	
Cylinders	2	2	2	4	4	4	4	4	4	6	
Min Depth Under	7in	7in	8in	8in	8in	8in	10in	10in	10in	10in	
Keel/Skeg (typ)	18cm	18cm	23cm	23cm	23cm	23cm	25cm	25cm	25cm	25cm	
Shallow Water Min Depth Under	0-3in 0-8cm	0-3in 0-8cm	0-3in 0-8cm	0-3in 0-8cm	0-3in 0-8cm	0-3in 0-8cm	N/A	N/A	N/A	N/A	
Keel/Skeg (typ)							"Frame width measured outside edges of leg sleeves ""Frame length measured front of forward crossbeam to back of rear crossbeam				
Capacity at:	SLX5010B4	SLX6512B4	SLX8012B4	SLX9012B5	SLX10014B5	SLX12016B5	SLX16018C5	SLX20020C5	SLX24022C5	SLX30022C5	
3ft .91m	5000lb 2268kg	6500lb 2948kg	8000lb 3629kg	9000lb 4082kg	10000lb 4536kb	12000lb 5443kg	N/A	N/A	N/A	N/A	
4ft	5000lb	6500lb	8000lb	9000lb	10000lb	12000lb	16000lb	20000lb	24000lb	30000lb	
1.2m	2268kg	2948kg	3629kg	4082kg	4536kg	5443kg	7257kg	9072kg	10886kg	13608kg	
5ft	5000lb	6000lb	7400lb	9000lb	10000lb	12000lb	16000lb	20000lb	24000lb	30000lb	
1.52m	2268kg	2721kg	3357kg	4082kg	4536kg	5443kg	7257kg	9072kg	10886kg	13608kg	
6ft	4500lb	5000lb	6000lb	8500lb	9000lb	10000lb	16000lb	19000lb	20000lb	26000lb	
1.82m	2041kg	2268kg	2722kg	3856kg	4082kg	4536kg	7257kg	9072kg	9072kg	11793kg	
6.5ft	4000lb	4500lb	5500lb	7500lb	8000lb	9000lb	16000lb	17000lb	18000lb	24000lb	
2m	1814kg	2041kg	2495kg	3402kg	3629kg	4082kg	7257kg	7711kg	8165kg	10886kg	
	With B3 Config	Cut Range	Standard Range	With AR18 Accy.	With AR30 Accy.						

SUNLIFT X



FLOATLIFT Free-floating Hydraulic Boat Lift



HELIX-P Rotary Hydraulic Cable Lift SWIFTSHIELD

System

Automatic Cover



SUNLIFT LEGACY Original Hydraulic Free-standing Lift



SUNPORT2 PWC Drive-On Dock

BOAT MORE, BOAT EASIER, **BOAT BETTER.**

sunstreamboatlifts.com